

PERF - SYO 5W30

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices (Compatible with DPF).

APPLICATIONS :

This DEXOS 2TM approved oil is required for all new GM/OPEL/VAUXHALL/CHEVROLET diesel and gasoline models. GM/OPEL has advised that the dexos 2TM specification is backward compatible to older GM/OPEL specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/OPEL/VAUXHALL/CHEVROLET diesel and gasoline vehicles can use dexos 2TM lubricants. C2* meets all engine protection requirements of ACEA C2.

PERFORMANCE LEVEL :

- ACEA C2/C3
- API SN/CF
- BMW LL-04
- VW 502 00/505 00/505 01
- OPEL OV0401547
- GM DEXOS 2TM
- MB 229.51
- MB 229.52
- RN17 LEVEL

CHARACTERISTICS :

TEST	unit	average value
Density at 15 °C	kg/l	0.851
Viscosity -30 °C	mPas	6136
Viscosity 40 °C	mm ² /s	72.60
Viscosity 100 °C	mm ² /s	12.50
Viscosity Index		172
Flash Point COC	°C	230
Pour Point	°C	-36
Total Base Number	mgKOH/g	7.4
Sulphate Ash	%	0.78